



No	L	CABLE
DW-F5E-0025-BL	250 ± 40mm	CAT. 5E/FTP 26AWG, BLUE
DW-F5E-005-BL	500 ± 40mm	CAT. 5E/FTP 26AWG, BLUE
DW-F5E-010-BL	1000 ± 40mm	CAT. 5E/FTP 26AWG, BLUE
DW-F5E-020-BL	2000 ± 40mm	CAT. 5E/FTP 26AWG, BLUE

- NOTES:
1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
 2. CONDUCTOR RESISTANCE: 10 OHMS MAX.
 3. INSULATOR RESISTANCE: 5M OHMS MIN, DC 300V 0.01sec.
 4. HI-POT: DC 300V 0.1sec.

3	Cable	CAT. 5E/FTP CABLE 26AWG (7/0.16)*4P+AL+D (7/0.12BS) JACKET: PVC, BLUE; OD: 5.5 ± 0.2mm	1
2	Molding	45P PVC OUTER MOLDING HOUSING, COLOR: BLUE	2
1	Connector	RJ45 MALE CONNECTOR (SHIELD), PIN GOLD PLATED 3U".	2
NO	PART NAME	DESCRIPTION	QTY

-TOLERANCES- UNLESS OTHERWISE SPECIFIED						
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm				PART DESCRIPTION: Patch Cable CAT5E FTP PVC 0,5m Blue Non-Snag-Proof		
		Appd: JIM KING		P/N: DW-F5E-005-BL		
Check:		Date	Scale	Unit	Type	Page
Draw: Gavin		2022.11.30	Free	MM	Z	1/1

1

2

3

4

5

6