


SmartAX EA5801-GP08

Optimized Lightweight OLT for Rapid Network Construction

- The EA5801-GP08 provides GPON access, and it provides a unified carrying platform for multiple services, including broadband, voice, video, and monitoring.
- The EA5801-GP08 supports POL and FTTH network construction modes. It carries all services over one fiber network, simplifying network architecture and reducing OPEX.
- The EA5801-GP08 can be installed in indoors or outdoors cabinets. When installed outdoors, it can be easily deployed in high temperatures, conserving man power and cabinet space.

Light-Weight OLT, Adapting to Various Scenarios

The EA5801-GP08 is a box-shaped OLT that requires 1 U installation space, making it applicable to access point convergence on a small scale. It is suitable for lightweight deployment in enterprises. One OLT can meet the service-carrying requirements for an enterprise or campus.



Technical Specifications

Product	
Specification	EA5801-GP08
Dimensions (H x W x D)	Without mounting ears: 43.6 mm x 442 mm x 222.3 mm With IEC-standard mounting ears: 43.6 mm x 482.6 mm x 222.3 mm With ETSI-standard mounting ears: 43.6 mm x 535 mm x 222.3 mm
Power supply mode	<ul style="list-style-type: none"> DC power supply (dual for backup) AC power supply (dual for backup)
Working voltage range	<ul style="list-style-type: none"> DC power supply: -38.4 V to -72 V AC power supply: 100 V to 240 V
Rated voltage	<ul style="list-style-type: none"> DC power supply: -48 V/-60 V AC power supply: 110 V/220 V
Maximum input current	<ul style="list-style-type: none"> DC power supply: 6 A AC power supply: 2.5 A
Ambient temperature	-40°C to +65°C* (normal operation) Minimum startup temperature: -25°C *+65°C indicates the temperature of the air intake vent of the service subrack.
Ambient humidity	5% RH to 95% RH
Atmospheric pressure	70 kPa to 106 kPa
Altitude	< 4000 m** **The air density varies with the altitude and will affect the heat dissipation of a device. Therefore, the working environment temperature of the device varies with the altitude.
System Layer 2 packet forwarding rate	13 Mpps
MAC addresses	32768
Access ONT	1024
IPv4 routing table	8192
IPv6 routing table	4096
ARP table	16384
GE upstream ports	2 optical/electrical combo ports
10GE/GE upstream ports	2
Number of service ports	8*GPON

More

Access products:

<http://e.huawei.com/en/products/fixed-network/access>

Huawei products:

<http://support.huawei.com/enterprise>



Access Products



Huawei Enterprise Support

Copyright © Huawei Technologies Co.,Ltd. 2018. All rights reserved.

General disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. there are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

<http://www.huawei.com>